



HeritageTM
INDUSTRIAL




PULLOUT DOWEL PINS

Quality without Compromise

Pullout Dowel Pins, Engineered for Easy Installation and Removal

Our **Pullout Dowel Pins** assure the same great performance as standard dowel pins with the added benefit of a threaded hole at one end to assist with installation and removal.


The **Flat Vent Metric Pullout Dowel Pins** (DIN 7979D) model offers the same benefit with the addition of a slightly flattened side to allow gas or liquid to escape while the medium is displaced during insertion.



Outside Diameter (A)
Overall Length (B)
Thread Size (X)

Alloy Steel Construction

- Hardness rating of HRC 58-62
- For use in dry environments



Outside Diameter (A)
Overall Length (B)
Thread Size (X)


Item #	Overall Length (B)
3/16" Diameter (A) Thread Size (X): #8-32	
DOWP-187-0500	1/2"
1/4" Diameter (A) Thread Size (X): #8-32	
DOWP-250-0500	1/2"
DOWP-250-0750	3/4"
DOWP-250-1000	1"
DOWP-250-1250	1-1/4"
DOWP-250-1500	1-1/2"
DOWP-250-1750	1-3/4"
DOWP-250-2000	2"
DOWP-250-2250	2-1/4"
DOWP-250-2500	2-1/2"
5/16" Diameter (A) Thread Size (X): #10-32	
DOWP-312-0750	3/4"
DOWP-312-1000	1"
DOWP-312-1250	1-1/4"
DOWP-312-1500	1-1/2"
DOWP-312-2000	2"
DOWP-312-2250	2-1/4"
DOWP-312-2500	2-1/2"
DOWP-312-3000	3"
3/8" Diameter (A) Thread Size (X): #10-32	
DOWP-375-0750	3/4"
DOWP-375-1000	1"
DOWP-375-1250	1-1/4"
DOWP-375-1500	1-1/2"
DOWP-375-1750	1-3/4"
DOWP-375-2000	2"
DOWP-375-2250	2-1/4"
DOWP-375-2500	2-1/2"
DOWP-375-2750	2-3/4"
DOWP-375-3000	3"
DOWP-375-3500	3-1/2"

Item #	Overall Length (B)
1/2" Diameter (A) Thread Size (X): 1/4"-20	
DOWP-500-1000	1"
DOWP-500-1250	1-1/4"
DOWP-500-1500	1-1/2"
DOWP-500-1750	1-3/4"
DOWP-500-2000	2"
DOWP-500-2250	2-1/4"
DOWP-500-2500	2-1/2"
DOWP-500-3000	3"
DOWP-500-3500	3-1/2"
DOWP-500-4000	4"
DOWP-500-5000	5"
5/8" Diameter (A) Thread Size (X): 1/4"-20	
DOWP-625-1000	1"
DOWP-625-1500	1-1/2"
DOWP-625-2000	2"
DOWP-625-3000	3"
DOWP-625-3500	3-1/2"
DOWP-625-4000	4"
3/4" Diameter (A) Thread Size (X): 5/16"-18	
DOWP-750-1000	1"
DOWP-750-1250	1-1/4"
DOWP-750-1500	1-1/2"
DOWP-750-1750	1-3/4"
DOWP-750-2000	2"
DOWP-750-2500	2-1/2"
DOWP-750-3000	3"
DOWP-750-3500	3-1/2"
DOWP-750-4000	4"
DOWP-750-5000	5"
1" Diameter (A) Thread Size (X): 5/16"-18	
DOWP-1000-2000	2"
DOWP-1000-2500	2-1/2"
DOWP-1000-3000	3"
DOWP-1000-4000	4"


Item #	Overall Length (B)
M4 Diameter (A) Thread Size (X): M2-0.4	
DOWPFM-040-010	10.00 mm
DOWPFM-040-012	12.00 mm
DOWPFM-040-014	14.00 mm
DOWPFM-040-016	16.00 mm
DOWPFM-040-018	18.00 mm
DOWPFM-040-020	20.00 mm
DOWPFM-040-024	24.00 mm
DOWPFM-040-025	25.00 mm
DOWPFM-040-028	28.00 mm
DOWPFM-040-030	30.00 mm
DOWPFM-040-032	32.00 mm
M5 Diameter (A) Thread Size (X): M3-0.5	
DOWPFM-050-010	10.00 mm
DOWPFM-050-012	12.00 mm
DOWPFM-050-014	14.00 mm
DOWPFM-050-016	16.00 mm
DOWPFM-050-020	20.00 mm
DOWPFM-050-024	24.00 mm
DOWPFM-050-025	25.00 mm
DOWPFM-050-028	28.00 mm
DOWPFM-050-032	32.00 mm
M6 Diameter (A) Thread Size (X): M4-0.7	
DOWPFM-060-010	10.00 mm
DOWPFM-060-012	12.00 mm
DOWPFM-060-014	14.00 mm
DOWPFM-060-016	16.00 mm
DOWPFM-060-018	18.00 mm
DOWPFM-060-020	20.00 mm
DOWPFM-060-024	24.00 mm
DOWPFM-060-025	25.00 mm
DOWPFM-060-028	28.00 mm
DOWPFM-060-030	30.00 mm
DOWPFM-060-035	35.00 mm
DOWPFM-060-036	36.00 mm
DOWPFM-060-040	40.00 mm
DOWPFM-060-045	45.00 mm
DOWPFM-060-050	50.00 mm
DOWPFM-060-060	60.00 mm

Item #	Overall Length (B)
M8 Diameter (A) Thread Size (X): M5-0.8	
DOWPFM-080-012	12.00 mm
DOWPFM-080-016	16.00 mm
DOWPFM-080-018	18.00 mm
DOWPFM-080-020	20.00 mm
DOWPFM-080-024	24.00 mm
DOWPFM-080-025	25.00 mm
DOWPFM-080-028	28.00 mm
DOWPFM-080-030	30.00 mm
DOWPFM-080-032	32.00 mm
DOWPFM-080-035	35.00 mm
DOWPFM-080-040	40.00 mm
DOWPFM-080-045	45.00 mm
DOWPFM-080-050	50.00 mm
DOWPFM-080-055	55.00 mm
DOWPFM-080-060	60.00 mm
DOWPFM-080-070	70.00 mm
DOWPFM-080-080	80.00 mm
M10 Diameter (A) Thread Size (X): M6-1	
DOWPFM-100-020	20.00 mm
DOWPFM-100-024	24.00 mm
DOWPFM-100-025	25.00 mm
DOWPFM-100-028	28.00 mm
DOWPFM-100-030	30.00 mm
DOWPFM-100-032	32.00 mm
DOWPFM-100-035	35.00 mm
DOWPFM-100-036	36.00 mm
DOWPFM-100-040	40.00 mm
DOWPFM-100-045	45.00 mm
DOWPFM-100-050	50.00 mm
DOWPFM-100-055	55.00 mm
DOWPFM-100-060	60.00 mm
DOWPFM-100-070	70.00 mm
DOWPFM-100-090	90.00 mm
DOWPFM-100-100	100.00 mm

Item #	Overall Length (B)
M12 Diameter (A) Thread Size (X): M6-1	
DOWPFM-120-024	24.00 mm
DOWPFM-120-025	25.00 mm
DOWPFM-120-028	28.00 mm
DOWPFM-120-030	30.00 mm
DOWPFM-120-032	32.00 mm
DOWPFM-120-035	35.00 mm
DOWPFM-120-040	40.00 mm
DOWPFM-120-045	45.00 mm
DOWPFM-120-050	50.00 mm
DOWPFM-120-055	55.00 mm
DOWPFM-120-060	60.00 mm
DOWPFM-120-070	70.00 mm
DOWPFM-120-080	80.00 mm
DOWPFM-120-090	90.00 mm
DOWPFM-120-100	100.00 mm
M16 Diameter (A) Thread Size (X): M8-1.25	
DOWPFM-160-030	30.00 mm
DOWPFM-160-032	32.00 mm
DOWPFM-160-036	36.00 mm
DOWPFM-160-040	40.00 mm
DOWPFM-160-050	50.00 mm
DOWPFM-160-055	55.00 mm
DOWPFM-160-060	60.00 mm
DOWPFM-160-070	70.00 mm
DOWPFM-160-080	80.00 mm
DOWPFM-160-090	90.00 mm
DOWPFM-160-100	100.00 mm
M20 Diameter (A) Thread Size (X): M10-1.5	
DOWPFM-200-036	36.00 mm
DOWPFM-200-040	40.00 mm
DOWPFM-200-050	50.00 mm
DOWPFM-200-055	55.00 mm
DOWPFM-200-060	60.00 mm
DOWPFM-200-080	80.00 mm
DOWPFM-200-090	90.00 mm
DOWPFM-200-100	100.00 mm
M25 Diameter (A) Thread Size (X): M16-2	
DOWPFM-250-045	45.00 mm
DOWPFM-250-090	90.00 mm
DOWPFM-250-120	120.00 mm



Do not apply main load to threaded portion of pin.



Dowel pins must be harder than their host material to prevent deformation during installation.

Additional sizes available upon request for special orders

* Some Exclusions Apply

